



WCR3 CPP Tx Power Monitor, Profile Time Interval, HotLoad/WarmLoad Ratios

UTC: 21:25:45-21:32:40, TimeCor: 0.00s, Dur: 415.00s
 TimeFlg: 1, TFPstatus constant.
 TimeInt/PPS(min,max,mn,std): 60.0,60.0,60.0,0.0 ms / 16.7,16.7,16.7
 NumRec(r/t): 6916/6916, 0-6915/21:25:45-21:32:40
 AcqTime: 60.0ms, Rate: 0.123MB/s, Averages (req.,actual): 400,400
 Pulse: 250ns, IFF: 4.0MHz, Tx: H1 H1 H1
 PRF: 20.0 20.0 KHz, IGS: 50us
 Range(min,max,rqs): 105, 6288, 15.0 m, Gates: 413, Aspect: 2.8
 Mirror(-9|0|1|2,3,9x = no mirror|sidelup|error): 1




WCR3 CPP Temperature Monitor: Hot Loads, Warm Loads, Modulator, and EIK

mintempC(VrxHL,HrxHL,VrxWL,HrxWL,Mod,EIK): 91,93,24,26,25,23
 maxtempC(VrxHL,HrxHL,VrxWL,HrxWL,Mod,EIK): 92,93,25,28,25,25
 LOalarm(20,240,2817,14861 MHz): None
 EIK/Modulator Faults: None




WCR3 CPP Receivers Gain and Noise Figure

Rx Saturation: 0 pixs, 0 gates, 0 profs, 0 prod(s)




WCR3 CPP RM pulses(Tx is OFF) received power: Mean, StDev(all gates)

	Min	Max	Mean	Median	StDev
RMPHrxH1 (mean_dBm)	-65.16	-65.16	-65.16	-65.16	-NaN
RMPHrxH1 (std_dBm)	-76.90	-76.90	-76.90	-76.90	-NaN




WCR3 CPP Receivers Noise Power from the Warm Loads Measurements

	Min	Max	Mean	Median	StDev
Hrx, H1(WL [dBm])	-65.46	-64.35	-64.88	-64.89	-79.40




WCR3 CPP Receivers Noise Power from the Hot Loads Measurements

Hrx, H1(HL [dBm])	Min	Max	Mean	Median	StDev
	-65.25	-64.12	-64.68	-64.68	-79.20




WCR3 CPP Receivers Noise Power from the Sky/RM Measurements

	Min	Max	Mean	Median	StDev
Hrx, H1(RM [dBm])	-65.56	-59.53	-64.54	-64.82	-71.31




WCR3 CPP "Best" estimate Receivers Noise Power


	Min	Max	Mean	Median	StDev
H1WL5_0 [dBm]	-65.46	-64.35	-64.88	-64.89	-79.40




WCR3 CPP Averaged Received power for all recorded gates
blue: 212545-212912, 3459 profiles averaged
red: 212912-213240, 3458 profiles averaged



WCR3 CPP Averaged Power for neg. gates & up to 100 gates
blue: 212545-212912, 3459 profiles averaged
red: 212912-213240, 3458 profiles averaged




WCR3 CPP Receivers Phase Noise (in m/s) from the Warm Loads Measurements



WCR3 CPP Received Power Products for Range gate 5 (180.4 m)

	Min	Max	Mean
up(hh [dBm])	-17.56	-4.11	-9.35



WCR3 CPP Doppler Velocity Products at180.4 m range

	Min	Max	Mean	StDev
b1u, hhhh(rg5[m/s])	0.53	6.03	3.55	0.74