


WCR3 CPP Tx Power Monitor, Profile Time Interval, HotLoad/WarmLoad Ratios


UTC: 20:46:38-22:14:02, TimeCor: 0.00s, Dur: 1152.23s  
 TimeFlg: 1, TFPstatus constant.  
 TimeInt/PPS(min,max,mn,std): 60.0,60.0,60.0,0.0 ms / 16.7,16.7,16.7  
 NumRec(r/t): 19200/87394, 57600-76799/21:44:14-22:03:27  
 AcqTime: 60.0ms, Rate: 0.123MB/s, Averages (req.,actual): 400,400  
 Pulse: 250ns, IFF: 4.0MHz, Tx: H1 H1 H1  
 PRF: 20.0 20.0 KHz, IGS: 50us  
 Range(min,max,rgs): 105, 6288, 15.0 m, Gates: 413, Aspect: 2.8  
 Mirror(-9|0|1|2,3,9x = no mirror|sidelup|error): 1



WCR3 CPP Temperature Monitor: Hot Loads, Warm Loads, Modulator, and EIK


mintempC(VrxHL,HrxHL,VrxWL,HrxWL,Mod,EIK): 91,92,24,27,26,27  
 maxtempC(VrxHL,HrxHL,VrxWL,HrxWL,Mod,EIK): 91,92,25,27,27,28  
 LOalarm(20,240,2817,14861 MHz): None

EIK Faults(# prof affected):  
 DeckT,CollT,BodyCurr,Fault2,DeckF,OverDuty,HVPS,Fault1 (86,86,86,86,86,86,86)




WCR3 CPP Receivers Gain and Noise Figure

Rx Saturation: 0 pixs, 0 gates, 0 profs, 0 prod(s)




WCR3 CPP RM pulses(Tx is OFF) received power: Mean, StDev(all gates)

	Min	Max	Mean	Median	StDev
RMPHrxH1(mean_dBm)	-65.06	-65.06	-65.06	-65.06	-126.57
RMPHrxH1(std_dBm)	-77.77	-77.77	-77.77	-77.77	-140.73




WCR3 CPP Receivers Noise Power from the Warm Loads Measurements

	Min	Max	Mean	Median	StDev
Hrx, H1(WL [dBm])	-65.26	-64.13	-64.68	-64.68	-79.21




WCR3 CPP Receivers Noise Power from the Hot Loads Measurements

	Min	Max	Mean	Median	StDev
Hrx, H1(HL [dBm])	-65.11	-63.93	-64.49	-64.50	-79.01



WCR3 CPP Receivers Noise Power from the Sky/RM Measurements


Hrx, H1(RM [dBm])	Min	Max	Mean	Median	StDev
	-65.63	-61.81	-64.42	-64.52	-73.16




WCR3 CPP "Best" estimate Receivers Noise Power

	Min	Max	Mean	Median	StDev
H1RG100_0 [dBm]	-65.71	-64.55	-65.10	-65.10	-79.61







WCR3 CPP Averaged Received power for all recorded gates  
blue: 214414-215350, 9601 profiles averaged  
red: 215350-220327, 9600 profiles averaged



WCR3 CPP Averaged Power for neg. gates & up to 100 gates  
blue: 214414-215350, 9601 profiles averaged  
red: 215350-220327, 9600 profiles averaged




WCR3 CPP Receivers Phase Noise (in m/s) from the Warm Loads Measurements



WCR3 CPP Received Power Products for Range gate 5 (180.4 m)

	Min	Max	Mean
up(hh [dBm])	-65.70	-43.58	-63.72



WCR3 CPP Doppler Velocity Products at 180.4 m range

	Min	Max	Mean	StDev
b1u, hhhh(rg5[m/s])	-15.78	15.79	0.04	8.11